

**AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims**

**Claim 1 (currently amended):** An opening/closing type communication terminal, comprising:

a hinge portion, which couples two casing members so as to freely open and close,

wherein the hinge portion includes:

a first rotating member, which serves as an axis for rotating the two casing members in a predetermined direction;

a second rotating member, which serves as an axis for rotating one casing member of the two casing members relative to the other casing member of the two casing members in a direction perpendicular to a rotating direction in which the first rotating member serves as the axis; and

a cover member, which covers the first rotating member and the second rotating member; and

wherein the cover member is fixed to the first rotating member;

wherein a cable derived from the one casing member extends in the first rotating member along an axis direction of the first rotating member; and

wherein the cable is derived from one end portion of the first rotating member to insert into the other casing member.

**Claim 2 (previously presented):** The opening/closing type communication terminal as set forth in claim 1, further comprising a rotating movement restricting member which is provided in a vicinity of a center of axis of the first rotating member, and which restricts both the rotating movement in which the first rotating member serves as the axis and the rotating movement in which the second rotating member serves as the axis in accordance with a condition of the two casing members.

**Claim 3 (previously presented):** The opening/closing type communication terminal as set forth claim 2, wherein a stable condition of the communication terminal restricted by the rotating movement restricting member corresponds to any one of:

a condition in which the two casing members are folded so as to be opposed to each other;

a first opened condition in which the communication terminal under the folded condition is opened by rotating the two casing members up to a first predetermined angle while the first rotating member serves as the axis; and

a second opened condition in which the two casing members are rotated from the first opened condition up to a second

predetermined angle while the second rotating shaft serves as the axis.

**Claim 4 (previously presented):** The opening/closing type communication terminal as set forth in claim 3, wherein the rotating movement restricting member restricts the rotating movement while the second rotating member serves as the axis to a predetermined direction and at the second predetermined angle under the first opened condition;

wherein the rotating movement restricting member prohibits the rotating movement while the first rotating shaft serves as the axis under the second opened condition, and restricts the rotating movement while the second rotating member serves as the axis to a direction opposite to the second predetermined direction and at the second predetermined angle under the second opened condition; and

wherein the rotating movement restricting member prohibits the rotating movement while the second rotating member serves as the axis under a condition from the folded condition up to the first opened condition.

**Claim 5 (currently amended):** The opening/closing type communication terminal as set forth in claim 3, wherein the

cover member is fixed to the first rotating member by a fastening screw; and

wherein the fastening screw fixes the cover member to the first rotating member at a position that the fastening screw is covered by the casing members under both the folded condition and the first opened condition, and that the fastening screw is exposed ~~under a condition from the first opened condition up to~~ in the second opened condition.

**Claim 6 (previously presented):** The opening/closing type communication terminal as set forth in claim 3, wherein the second predetermined angle is 180 degrees at which the casing members are rotated so as to become the second opened condition from the first opened condition while the second rotating member serves as the axis;

wherein the communication terminal includes a condition detecting member which detects either the first opened condition or the second opened condition of the communication terminal;

wherein one of the two casing members includes a camera unit and a first display unit capable of displaying a picture photographed by the camera unit on one plane thereof, and includes a second display unit capable of displaying a picture formed based upon the picture photographed by the camera unit on another plane opposite to the one plane;

wherein the first display unit displays a mirror image as to the picture photographed by the camera unit under either the folded condition or the first opened condition; and

wherein the first display unit displays the mirror image as to the picture photographed by the camera unit, and the second display unit displays an inverted mirror image of the mirror image under the second opened condition.

**Claim 7 (previously presented):** A hinge apparatus which is adapted to constitute the hinge portion of the opening/closing type communication terminal according to any one of claim 1 to claim 6.